



# 04




## IMPACT TOOLS



Impact-Tools 1/4" _____	Page 206
Impact-Tools 3/8" _____	Page 209
Impact-Tools 1/2" _____	Page 212
Impact-Tools 3/4" _____	Page 219
Impact-Tools 1" _____	Page 224
Impact-Tools 1.1/2" + 2.1/2" _____	Page 228
Impact bits _____	Page 230

**788-..., 788A-...**
**IMPACT SOCKET 1/4", HEXAGON**

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 6,3, ISO 1174
- according to DIN 3129, ISO 2725-2


**6,3**
**1/4"**



Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0788000405100	788-4	23	4	7,5	13	7883-11	7884-11	6	14
0788000455100	788-4,5	23	4	8	13	7883-11	7884-11	6	14
0788000505100	788-5	23	5	8,5	13	7883-11	7884-11	6	14
0788000555100	788-5,5	23	5	9	13	7883-11	7884-11	6	14
0788000605100	788-6	23	6	10	13	7883-11	7884-11	6	14
0788000705100	788-7	23	6	11	13	7883-11	7884-11	6	15
0788000805100	788-8	23	7	12	13	7883-11	7884-11	6	15
0788000905100	788-9	23	7	13	13	7883-11	7884-11	6	15
0788001005100	788-10	23	7	14,5	13	7883-11	7884-11	6	17
0788001105100	788-11	23	8	16	13	7883-11	7884-11	6	17
0788001205100	788-12	23	9	17	13	7883-11	7884-11	6	18
0788001305100	788-13	23	9	18	13	7883-11	7884-11	6	18
0788001405100	788-14	23	9	20	13	7883-11	7884-11	6	24
0788001705100	788-17	26	10	24	13	7883-11	7884-11	6	35



Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0788100135100	788A-1/4	23	5	10,5	13	7883-11	7884-11	6	15
0788100175100	788A-5/16	23	5	12	13	7883-11	7884-11	6	15
0788100185100	788A-11/32	23	5	13	13	7883-11	7884-11	6	15

**796-E...**
**IMPACT SOCKET 1/4"**

- for outside TORX® screws
- for power tools
- special steel, phosphated
- female square according to DIN 3121-G6, 3, ISO 1174
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA


**6,3**
**1/4"**

Code	Number	★ mm	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0796000045000	796-E4	3,86	23	3,2	7,4	13	7883-11	7884-11	6	15
0796000055000	796-E5	4,73	23	3,2	8,3	13	7883-11	7884-11	6	15
0796000065000	796-E6	5,74	23	4	9,3	13	7883-11	7884-11	6	15
0796000075000	796-E7	6,16	23	4,8	9,8	13	7883-11	7884-11	6	15
0796000085000	796-E8	7,52	23	5,6	11,1	13	7883-11	7884-11	6	15
0796000105000	796-E10	9,42	23	6,4	13	13	7883-11	7884-11	6	16

### 7900-...

#### IMPACT EXTENSION BAR 1/4"

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square according to DIN 3121, form F and G, ISO 1174



6,3

1/4"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7900000505100	7900-50	50	7883-11	7884-11	6	28

### 7907-...

#### IMPACT ADAPTOR

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square according to DIN 3121, form F and G, ISO 1174



6,3

1/4"

Code	Number	□	■	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7907100175100	7907-5/16	1/4"	5/16"	25	7883-11	7884-11	3	18
7907100195100	7907-3/8	1/4"	3/8"	25	7883-11	7884-11	3	20

04

You will find the matching socket rails on page no. 139



## 4140-...

### ADAPTOR 1/4"

- for power tools
- **ELORA-Nr. 4140-50:** male square drive according to DIN 3121 E 6,3, ISO 1174 with locking pin, according to DIN 7428, ISO 3317
- **ELORA-Nr. 4140-100:** male square drive according to DIN 3120 A 6,3, ISO 1174 with ball locking device

6,3

1/4"



4140-50

4140-100

Code	Number	l/mm ┆┆┆			Pieces 	Weight/g 
4140000505200	4140-50	50	1/4"	1/4"	6	15,6
4140001005200	4140-100	100	1/4"	1/4"	6	38,0

## 7883-.../7884-...

### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKET 1/4"

- for locking impact sockets and operating tools
- locking pin made of alloyed special steel
- locking ring made of rubber elastic and oil resistant material




7883-...

7884-...

Code	Number	l/mm ┆┆┆	mm Ø	Pieces 	Weight/g 
7883000115100	7883-11	11	1,5	12	0,2
7883000135100	7883-13	13	1,5	12	0,2
7884000115100	7884-11	-	11	12	0,2
7884000145100	7884-14	-	14	12	0,2

**789-.../789A-...**
**IMPACT SOCKET 3/8", HEXAGON**

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 10, ISO 1174
- according to DIN 3129, ISO 2725-2


**10**
**3/8"**


Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0789000605100	789-6	32	5	11,3	19	7893-15	7894-15	6	40
0789000705100	789-7	32	5	12,5	19	7893-15	7894-15	6	40
0789000805100	789-8	32	6	13,7	19	7893-15	7894-15	6	40
0789000905100	789-9	32	6	15,0	19	7893-15	7894-15	6	40
0789001005100	789-10	32	7	16,3	19	7893-15	7894-15	6	41
0789001105100	789-11	32	7	17,5	19	7893-15	7894-15	6	41
0789001205100	789-12	32	8	19,0	19	7893-15	7894-15	6	58
0789001305100	789-13	32	8	20,0	22	7893-18	7894-18	6	40
0789001405100	789-14	32	9	21,3	22	7893-18	7894-18	6	58
0789001505100	789-15	32	9	22,5	22	7893-18	7894-18	6	58
0789001605100	789-16	32	10	23,8	22	7893-18	7894-18	6	58
0789001705100	789-17	32	10	25,0	22	7893-18	7894-18	6	66
0789001805100	789-18	32	11	26,3	22	7893-18	7894-18	6	66
0789001905100	789-19	32	12	27,5	22	7893-18	7894-18	6	66
0789002005100	789-20	34	12	29,0	22	7893-18	7894-18	6	75
0789002105100	789-21	34	13	30,0	22	7893-18	7894-18	6	75
0789002205100	789-22	34	14	31,3	22	7893-18	7894-18	6	75
0789002305100	789-23	34	15	32,5	22	7893-18	7894-18	6	75
0789002405100	789-24	36	16	33,8	22	7893-18	7894-18	6	75




Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0789100175100	789A-5/16	29,5	5	12,5	19	7893-15	7894-15	6	40
0789100215100	789A-7/16	29,5	7	17,0	19	7893-15	7894-15	6	41
0789100235100	789A-1/2	29,5	7	20,0	19	7893-15	7894-15	6	55
0789100245100	789A-9/16	31,5	8	22,0	22	7893-18	7894-18	6	56

### 797-E...

#### IMPACT SOCKET 3/8"

- for outside TORX® screws
- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 10, ISO 1174
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



10


3/8"

Code	Number	mm	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0797000045000	797-E4	3,86	32	5	9	19	7893-15	7894-15	6	43
0797000055000	797-E5	4,73	32	5	9	19	7893-15	7894-15	6	43
0797000065000	797-E6	5,74	32	7	10	19	7893-15	7894-15	6	42
0797000075000	797-E7	6,16	32	7	10	19	7893-15	7894-15	6	42
0797000085000	797-E8	7,52	32	8	10,5	19	7893-15	7894-15	6	42
0797000105000	797-E10	9,42	32	9	12,5	19	7893-15	7894-15	6	42
0797000125000	797-E12	11,17	32	10	15	19	7893-15	7894-15	6	42
0797000145000	797-E14	12,9	32	12	17,5	19	7893-15	7894-15	6	44
0797000165000	797-E16	14,76	32	12	19	19	7893-15	7894-15	6	42

### 789IN-...

#### IMPACT SCREWDRIVER SOCKET 3/8"

- for inside hexagon screws
- for power tools
- with exchangeable blades
- special steel, phosphated
- female square drive according to DIN 3121-G 10, ISO 1174



10

3/8"

Code	Number	l/mm	l1 mm	d mm	Locking Pin	Locking Ring	Pieces	Weight/g
0789010305100	789IN-3	48	20	19	7893-15	7894-15	6	35
0789010405100	789IN-4	48	20	19	7893-15	7894-15	6	35
0789010505100	789IN-5	48	20	19	7893-15	7894-15	6	40
0789010605100	789IN-6	48	20	19	7893-15	7894-15	6	40
0789010805100	789IN-8	55	25	19	7893-15	7894-15	6	55
0789011005100	789IN-10	60	28	19	7893-15	7894-15	6	70
0789011205100	789IN-12	65	31	19	7893-15	7894-15	6	90

Spare blades on request

### 7906-...

#### IMPACT EXTENSION BAR 3/8"

- for power tools
- special steel, phosphated
- square according to DIN 3121, form F and G, ISO 1174



10

3/8"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7906000755100	7906-75	75	7893-15	7894-15	6	87
7906001505100	7906-150	150	7893-15	7894-15	3	180
7906002505100	7906-250	250	7893-15	7894-15	3	286

You will find the matching socket rails on page no. 143



### 795-3/8

#### IMPACT UNIVERSAL JOINT 3/8"

- for power tools
- special steel, phosphated
- square according to DIN 3121, form F and G, ISO 1174



10

3/8"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
0795100195100	795-3/8	50	7893-18	7894-18	3	67

### 7902-.../7905-.../7907-...

#### IMPACT ADAPTOR

- for power tools
- special steel, phosphated
- square according to DIN 3121, form F, G and H, ISO 1174



10

3/8"

Code	Number	Ø	□	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7907100195100	7907-3/8	1/4"	3/8"	25	7883-11	7884-11	3	20
7905100235100	7905-1/2	3/8"	1/2"	32	7893-21	7894-20	3	75
7902100195100	7902-3/8	1/2"	3/8"	36	7903-20	7904-20	3	65

### 3426

#### IMPACT ADAPTOR

- for power tools
- with 1/4" outside hexagon according to DIN 3126-E 6,3, DIN ISO 1173
- special steel
- male square drive according to DIN 3121-E 10, ISO 1174, with locking pin
- according to DIN 7428, ISO 3317



10

3/8"

Code	Number	l/mm	□	Ø	Pieces	Weight/g
3426000000000	3426	50	3/8"	1/4"	6	52

### 7893-.../7894-...

#### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKET 3/8"


- for locking impact sockets and operating tools
- locking pin made of alloyed special steel
- locking ring made of rubber elastic and oil resistant material



Code	Number	l/mm	mm Ø	Pieces	Weight/g
7893000155100	7893-15	15	2,5	12	0,60
7893000185100	7893-18	18	2,5	12	0,75
7893000215100	7893-21	21	3,0	12	0,80
7894000155100	7894-15	-	15	12	0,30
7894000185100	7894-18	-	18	12	0,35
7894000205100	7894-20	-	20	12	0,30

**790-..., 790A-....**
**IMPACT SOCKET 1/2", HEXAGON**

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 12,5, ISO1174
- according to DIN 3129, ISO 2725-2


**12,5**
**1/2"**


Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790000105100	790-10	36	7	17,5	25	7903-20	7904-20	6	90
0790000115100	790-11	36	7	18,5	25	7903-20	7904-20	6	90
0790000125100	790-12	36	8	20	25	7903-20	7904-20	6	95
0790000135100	790-13	36	8	21	25	7903-20	7904-20	6	88
0790000145100	790-14	37	9	22,5	25	7903-20	7904-20	6	90
0790000155100	790-15	37	9	23,5	30	7903-25	7904-24	6	135
0790000165100	790-16	37	10	25	30	7903-25	7904-24	6	135
0790000175100	790-17	37	10	26	30	7903-25	7904-24	6	140
0790000185100	790-18	38	11	27,5	30	7903-25	7904-24	6	137
0790000195100	790-19	38	12	28,5	30	7903-25	7904-24	6	130
0790000205100	790-20	38	12	30	30	7903-25	7904-24	6	130
0790000215100	790-21	39	13	31	30	7903-25	7904-24	6	130
0790000225100	790-22	39	14	32,5	30	7903-25	7904-24	6	150
0790000235100	790-23	39	15	33,5	30	7903-25	7904-24	6	180
0790000245100	790-24	42	16	35	30	7903-25	7904-24	6	185
0790000255100	790-25	42	16	36	30	7903-25	7904-24	6	215
0790000265100	790-26	42	17	37,5	30	7903-25	7904-24	6	225
0790000275100	790-27	45	18	38,5	30	7903-25	7904-24	6	230
0790000285100	790-28	45	18	40	30	7903-25	7904-24	6	255
0790000295100	790-29	45	19	41	30	7903-25	7904-24	6	245
0790000305100	790-30	49	20	42,5	30	7903-25	7904-24	6	250
0790000325100	790-32	49	21	45	30	7903-25	7904-24	6	250
0790000345100	790-34	51	22	47,5	30	7903-25	7904-24	6	275




Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790100195100	790A-3/8	35	5	16,5	25	7903-20	7904-20	6	90
0790100215100	790A-7/16	35	7	18	25	7903-20	7904-20	6	90
0790100235100	790A-1/2	35	7	20	25	7903-20	7904-20	6	88
0790100245100	790A-9/16	35	8	22	25	7903-20	7904-20	6	135
0790100265100	790A-5/8	35	9	24	30	7903-25	7904-24	6	135
0790100275100	790A-11/16	35	10	26	30	7903-25	7904-24	6	137
0790100285100	790A-3/4	35	11	29	30	7903-25	7904-24	6	130
0790100305100	790A-13/16	38	13	31	30	7903-25	7904-24	6	130
0790100315100	790A-7/8	38	14	33	30	7903-25	7904-24	6	150
0790100325100	790A-15/16	38	15	35	36	7903-30	7904-30	6	185
0790100345100	790A-1	38	16	37	36	7903-30	7904-30	6	225
0790100355100	790A-1. 1/16	40	16	39	36	7903-30	7904-30	6	225
0790100365100	790A-1.1/8	50	18	41	36	7903-30	7904-30	6	255
0790100385100	790A-1 1/4	50	19	44	36	7903-30	7904-30	6	250
0790100395100	790A-1.5/16	50	20	46	36	7903-30	7904-30	6	290



## 790LT-...

### IMPACT SOCKET 1/2", EXTRA DEEP, HEXAGON

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 12,5, ISO 1174



12,5

1/2"



Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790020105100	790LT-10	85	12	17	25	7903-20	7904-20	6	155
0790020135100	790LT-13	85	14	21	25	7903-20	7904-20	6	160
0790020145100	790LT-14	85	15	22,5	25	7903-20	7904-20	6	185
0790000155100	790LT-15	85	15	23,5	30	7903-25	7904-24	6	210
0790020165100	790LT-16	85	15	25	30	7903-25	7904-24	6	210
0790020175100	790LT-17	85	15	26	30	7903-25	7904-24	6	230
0790020185100	790LT-18	85	16	27	30	7903-25	7904-24	6	240
0790020195100	790LT-19	85	16	28,5	30	7903-25	7904-24	3	250
0790020205100	790LT-20	85	19	30	30	7903-25	7904-24	3	260
0790020215100	790LT-21	85	19	31	30	7903-25	7904-24	3	275
0790020225100	790LT-22	85	19	32,5	30	7903-25	7904-24	3	300
0790020245100	790LT-24	85	21	35	30	7903-25	7904-24	3	370
0790020275100	790LT-27	85	23	38	30	7903-25	7904-24	3	430
0790020305100	790LT-30	85	25	42	30	7903-25	7904-24	3	510
0790020325100	790LT-32	85	25	44	30	7903-25	7904-24	3	560



Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790120195100	790LTA-3/8	78	4	16	25	7903-20	7904-20	6	140
0790120215100	790LTA-7/16	78	6	18	25	7903-20	7904-20	6	140
0790120235100	790LTA-1/2	78	6	20	25	7903-20	7904-20	6	140
0790120245100	790LTA-9/16	78	7	22	25	7903-25	7904-24	6	200
0790120265100	790LTA-5/8	78	8	25	25	7903-25	7904-24	6	200
0790120275100	790LTA-11/16	78	9	25	25	7903-25	7904-24	6	190
0790120285100	790LTA-3/4	78	9,5	28	30	7903-25	7904-24	3	250
0790120305100	790LTA-13/16	78	11	30	30	7903-25	7904-24	3	280
0790120315100	790LTA-7/8	78	13	32	30	7903-25	7904-24	3	280
0790120325100	790LTA-15/16	78	13	35	30	7903-25	7904-24	3	300
0790120345100	790LTA-1	78	13	35	30	7903-25	7904-24	3	380
0790120355100	790LTA-1.1/16	78	13	38	30	7903-25	7904-24	3	430
0790120365100	790LTA-1.1/8	78	16,5	38	30	7903-25	7904-24	3	480
0790120385100	790LTA-1.1/4	78	17	44	35	7903-25	7904-24	3	500
0790120395100	790LTA-1.5/16	78	19	45	35	7903-25	7904-24	3	550


You will find Impact Sockets 1/2" thin walled on page no. 443



## 798-E...

### IMPACT SOCKET 1/2"

- ▶ for outside TORX® screws
- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square according to DIN 3121-G 12,5, ISO 1174
- ▶ TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



12,5

1/2"

Code	Number	★ mm	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0798000105000	798-E10	9,42	38	9	15	25	7903-20	7904-20	6	84
0798000145000	798-E14	12,90	38	12	18,5	25	7903-20	7904-20	6	86
0798000185000	798-E18	16,70	38	12	22	25	7903-20	7904-20	6	90
0798000205000	798-E20	18,45	38	13	25	30	7903-25	7904-24	6	128
0798000245000	798-E24	22,16	38	17	28,5	30	7903-25	7904-24	6	142

04




▶ We also focus on little experts in sport and therefore support the Bambini football team of the SG Hackenberg 1973 in Remscheid!

## 790IN-...

### IMPACT SCREWDRIVER SOCKET 1/2"

- for inside hexagon screws
- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-G 12,5, ISO 1174
- inch sizes on request, resp. see price list



12,5

1/2"




Code	Number	l/mm	d mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790010505100	790IN-5	78	25	7903-20	7904-20	6	85
0790010605100	790IN-6	78	25	7903-20	7904-20	6	92
0790010805100	790IN-8	78	25	7903-20	7904-20	6	102
0790011005100	790IN-10	78	25	7903-20	7904-20	6	130
0790011205100	790IN-12	78	25	7903-25	7904-20	6	136
0790011405100	790IN-14	78	25	7903-25	7904-20	6	136
0790011705100	790IN-17	78	25	7903-25	7904-20	6	140
0790011905100	790IN-19	78	25	7903-25	7904-20	6	210

04

## 790TX-...

### IMPACT SCREWDRIVER SOCKET 1/2"

- for inside TORX® screws
- exchangeable blades
- for power tools
- special steel, gunmetal-finished
- female square drive according to DIN 3121-G 12,5, ISO 1174
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



12,5

1/2"

Code	Number	★ mm	l/mm	d mm	Locking Pin	Locking Ring	Pieces	Weight/g
0790015305101	790TX-30	5,52	42	25	7903-20	7904-20	6	110
0790015405101	790TX-40	6,65	42	25	7903-20	7904-20	6	120
0790015505101	790TX-50	8,83	42	25	7903-20	7904-20	6	130
0790015555101	790TX-55	11,22	42	25	7903-20	7904-20	6	130
0790015605101	790TX-60	13,25	42	25	7903-20	7904-20	6	140
0790015705101	790TX-70	15,53	42	25	7903-20	7904-20	6	140

### 7901-...

#### IMPACT EXTENSION BAR 1/2"

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square according to DIN 3121, form F and G, ISO 1174



12,5

1/2"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7901001255100	7901-125	125	7903-20	7904-20	3	270
7901002505100	7901-250	250	7903-20	7904-20	3	540

### 795-1/2

#### IMPACT UNIVERSAL JOINT 1/2"

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square according to DIN 3121, form F and G, ISO 1174



12,5

1/2"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
0795100235100	795-1/2	65	7903-25	7904-24	3	170

### 7902-.../7912-...

#### IMPACT ADAPTOR

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square according to DIN 3121, form F, G and H, ISO 1174



12,5

1/2"

Code	Number	□	■	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7905100235100	7905-1/2	3/8"	1/2"	32	7893-21	7894-20	3	75
7902100195100	7902-3/8	1/2"	3/8"	36	7903-20	7904-20	3	65
7902100285100	7902-3/4	1/2"	3/4"	50	7903-25	7904-24	3	162
7912100235100	7912-1/2	3/4"	1/2"	57	7913-29	7914-28	3	235

You will find the matching socket rails on page no. 169



### 3427

#### IMPACT ADAPTOR

- for power tools
- with 1/4" outside hexagon according to DIN 3126-E 6,3, ISO 1173
- special steel
- male square drive according to DIN 3121-E 12,5, DIN ISO 1174, with locking pin
- according to DIN 7428, ISO 3317



12,5

1/2"

Code	Number	l/mm ┌──┐	□ 1/2"	⬤ 1/4"	Pieces 📦	Weight/g ⚖️
3427000000000	3427	75	1/2"	1/4"	6	100

### 7903-.../7904-...

#### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKETS 1/2"

- for locking impact sockets and operating tools
- locking pin made of alloyed special steel
- locking ring made of rubber elastic and oil resistant material




Code	Number	l/mm ┌──┐	mm ∅	Pieces 📦	Weight/g ⚖️
7903000205100	7903-20	20	3,0	12	0,75
7903000255100	7903-25	25	3,0	12	0,80
7903000305100	7903-30	30	3,0	12	1,00
7904000205100	7904-20	-	20	12	0,50
7904000245100	7904-24	-	24	12	1,00
7904000305100	7904-30	-	30	12	1,50

### 790 S6...

#### IMPACT SOCKET SET 1/2"

- for power tools
- in black metal storage case with OMS-hard foam insert
- tools made of special steel, phosphated
- square according to DIN 3121, form F and G, ISO1174




Code	Number	Contents	Pieces	Weight/g
0790500605100	790 S6	Impact Sockets 1/2": 790- 10, 13, 17, 19, 24 mm Impact Extension Bar 1/2"; 7901-125	1	1262
0790600605100	790 S6A	Impact Sockets 1/2": 790A- 3/8, 1/2, 7/8, 3/4, 15/16" AF Impact Extension Bar 1/2": 7901-125	1	1300

### 790 S6LT

#### IMPACT SOCKET SET 1/2"

- for power tools
- in black metal storage case with OMS-hard foam insert
- square according to DIN 3121, form F and G, ISO1174
- tools made of special steel, phosphated




Code	Number	Contents	Pieces	Weight/g
0790520605100	790 S6LT	Impact Sockets, extra deep 1/2"; 790LT- 10, 13, 17, 19, 24 mm Impact Extension Bar 1/2"; 7901-125	1	1880

### 790 S12...

#### IMPACT SOCKET SET 1/2"

- for power tools
- in black metal storage case with OMS-hard foam insert
- square according to DIN 3121, form F and G, ISO1174
- tools made of special steel, phosphated




Code	Number	Contents	Pieces	Weight/g
0790501205100	790 S12	Impact Sockets, 1/2": 790- 10, 11, 13, 14, 17, 19, 21, 22, 23, 24 mm Impact Extension Bar 1/2", 7901-125 Impact Universal Joint 1/2", 795-1/2	1	2500
0790601205100	790 S12A	Impact Sockets, 1/2": 790A- 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 7/8, 15/16, 1" AF Impact Extension Bar 1/2", 7901-125 Impact Universal Joint 1/2", 795-1/2	1	2400

You will find the matching OMS-24 module on page no. 48



**791-..., 791A-...**
**IMPACT SOCKET 3/4", HEXAGON**

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-H 20, ISO 1174
- according to DIN 3129, ISO 2725-2


**20**
**3/4"**


Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0791000175100	791-17	50	10	30	44	7913-37	7914-36	3	365
0791000195100	791-19	50	12	32,5	44	7913-37	7914-36	3	370
0791000215100	791-21	51	13	35	44	7913-37	7914-36	3	380
0791000225100	791-22	51	14	37,5	44	7913-37	7914-36	3	395
0791000245100	791-24	52	16	39	44	7913-37	7914-36	3	380
0791000255100	791-25	52	16	40	44	7913-37	7914-36	3	380
0791000265100	791-26	53	17	41,5	44	7913-37	7914-36	3	370
0791000275100	791-27	53	18	42,5	44	7913-37	7914-36	3	385
0791000285100	791-28	53	18	44	44	7913-37	7914-36	3	390
0791000295100	791-29	53	19	45	44	7913-37	7914-36	3	390
0791000305100	791-30	53	20	46,5	44	7913-37	7914-36	3	390
0791000325100	791-32	56	21	49	44	7913-37	7914-36	1	471
0791000335100	791-33	56	21	50	44	7913-37	7914-36	1	496
0791000345100	791-34	56	22	51,5	44	7913-37	7914-36	1	511
0791000365100	791-36	56	24	54	44	7913-37	7914-36	1	529
0791000385100	791-38	56	25	56,5	44	7913-37	7914-36	1	584
0791000415100	791-41	57	26	60	44	7913-37	7914-36	1	607
0791000465100	791-46	62	28	66,5	44	7913-37	7914-36	1	750




Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0791100285100	791A-3/4	50	12	31,5	44	7913-37	7914-36	3	370
0791100305100	791A-13/16	50	14	34	44	7913-37	7914-36	3	380
0791100315100	791A-7/8	50	16	36	44	7913-37	7914-36	3	395
0791100325100	791A-15/16	50	16	38	44	7913-37	7914-36	3	380
0791100345100	791A-1	53	18	40	44	7913-37	7914-36	3	380
0791100355100	791A-1.1/16	53	18	42	44	7913-37	7914-36	3	385
0791100365100	791A-1.1/8	53	20	44	44	7913-37	7914-36	3	390
0791100375100	791A-1.3/16	53	20	46	44	7913-37	7914-36	3	390
0791100385100	791A-1.1/4	56	20	48	44	7913-37	7914-36	1	479
0791100395100	791A-1.5/16	56	23	50	44	7913-37	7914-36	1	494
0791100405100	791A-1.3/8	56	23	52	44	7913-37	7914-36	1	518
0791100415100	791A-1.7/16	56	23	54	44	7913-37	7914-36	1	558
0791100425100	791A-1.1/2	56	25	56	44	7913-37	7914-36	1	583
0791100445100	791A-1.5/8	57	25	59	44	7913-37	7914-36	1	628

further sizes on request

## 791LT-...

### IMPACT SOCKET 3/4", EXTRA DEEP, HEXAGON

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-H 20, ISO 1174
- inch sizes on request, resp. see price list



20

3/4"

mm


Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0791020175100	791LT-17	100	15	30	44	7913-37	7914-36	1	603
0791020195100	791LT-19	100	17	32,5	44	7913-37	7914-36	1	620
0791020225100	791LT-22	100	19	36,5	44	7913-37	7914-36	1	695
0791020245100	791LT-24	100	21	39	44	7913-37	7914-36	1	745
0791020275100	791LT-27	100	23	42,5	44	7913-37	7914-36	1	828
0791020305100	791LT-30	100	25	46,5	44	7913-37	7914-36	1	869
0791020325100	791LT-32	100	26	49	44	7913-37	7914-36	1	921
0791020335100	791LT-33	100	26	50	44	7913-37	7914-36	1	984
0791020345100	791LT-34	100	27	51,5	44	7913-37	7914-36	1	1001
0791020365100	791LT-36	100	29	54	44	7913-37	7914-36	1	1050
0791020385100	791LT-38	100	30	56,5	44	7913-37	7914-36	1	1187
0791020415100	791LT-41	100	31	60	44	7913-37	7914-36	1	1272
0791020465100	791LT-46	100	33	66,5	44	7913-37	7914-36	1	1581
0791020505100	791LT-50	90	27	70	54	7913-37	7914-36	1	1400
0791020555100	791LT-55	94	30	78	54	7913-37	7914-36	1	1800
0791020605100	791LT-60	98	33	82	54	7913-37	7914-36	1	1900
0791020655100	791LT-65	105	38	86	54	7913-37	7914-36	1	2000



### 791IN-...

#### IMPACT SOCKET 3/4"

- ▶ for power tools
- ▶ for inside hexagon screws
- ▶ special steel, phosphated
- ▶ female square according to DIN 3121-H 20, ISO 1174
- ▶ inch sizes on request, resp. see price list



20

3/4"



Code	Number	l/mm	d mm	Locking Pin	Locking Ring	Pieces	Weight/g
0791010105101	791IN-10	69	44	7913-37	7914-36	3	490
0791010125101	791IN-12	69	44	7913-37	7914-36	3	510
0791010145101	791IN-14	69	44	7913-37	7914-36	3	520
0791010175101	791IN-17	69	44	7913-37	7914-36	3	540
0791010195101	791IN-19	84	44	7913-37	7914-36	3	600
0791010225101	791IN-22	84	44	7913-37	7914-36	3	620
0791010245101	791IN-24	84	44	7913-37	7914-36	3	690

### 7911-...

#### IMPACT EXTENSION BAR 3/4"

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square drive according to DIN 3121, form F and H, ISO 1174



20

3/4"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7911001755100	7911-175	175	7913-37	7914-36	1	865
7911002505100	7911-250	250	7913-37	7914-36	1	1151
7911003255100	7911-325	325	7913-37	7914-36	1	1452

### 795-3/4

#### IMPACT UNIVERSAL JOINT 3/4"

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square drive according to DIN 3121, Form F and H, ISO 1174



20

3/4"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
0795100285100	795-3/4	105	7913-37	7914-36	1	606

## 7902-.../7912-.../7922-...

### IMPACT ADAPTOR

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ square according to DIN 3121, form F, G and H, ISO 1174



20

3/4"

Code	Number	□	□	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7902100285100	7902-3/4	1/2"	3/4"	50	7903-25	7904-24	3	162
7912100235100	7912-1/2	3/4"	1/2"	57	7913-37	7914-36	3	235
7912100345100	7912-1	3/4"	1"	62	7913-37	7914-36	3	340
7922100285100	7922-3/4	1"	3/4"	75	7923-42	7924-41	1	548

## 7913-.../7914-...

### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKET 3/4"

- ▶ for locking impact sockets and operating tools
- ▶ locking pin made of alloyed special steel
- ▶ locking ring made of rubber elastic and oil resistant material




Code	Number	l/mm	mm Ø	Pieces	Weight/g
7913000295100	7913-29	29	4,0	12	3,0
7913000375100	7913-37	37	4,0	12	3,8
7913000455100	7913-45	45	4,0	12	4,5
7914000285100	7914-28	-	28	12	1,2
7914000365100	7914-36	-	36	12	1,4
7914000465100	7914-46	-	46	12	1,6

### 791 S6LT

#### IMPACT SOCKET SET 3/4"

- ▶ for power tools
- ▶ in black metal storage case with OMS-hard foam insert
- ▶ female square drive according to DIN 3121-H 20, ISO1174
- ▶ tools made of special steel, phosphated




Code	Number	Contents	Pieces	Weight/g
0791520605100	791 S6LT	Impact Sockets, extra deep 3/4"; 791LT- 24, 27, 30, 32, 36, 41 mm	1	7360

### 791 S5...

#### IMPACT SOCKET SET 3/4"

- ▶ for power tools
- ▶ in black metal storage case with OMS-hard foam insert
- ▶ female square drive according to DIN 3121-H 20, ISO 1174
- ▶ tools made of special steel, phosphated




Code	Number	Contents	Pieces	Weight/g
0791500505100	791 S5	Impact Sockets 3/4"; 791- 19, 24, 27, 30, 32 mm	1	2850
0791600505100	791 S5A	Impact Sockets 3/4"; 791A- 3/4, 15/16, 1.1/16, 1-3/16, 1.5/16" AF	1	2800

### 791 S10...

#### IMPACT SOCKET SET 3/4"

- ▶ for power tools
- ▶ in black metal storage case with OMS-hard foam insert
- ▶ female square drive according to DIN 3121-H 20, ISO1174
- ▶ tools made of special steel, phosphated




Code	Number	Contents	Pieces	Weight/g
0791501005100	791 S10	Impact Sockets 3/4": 791- 17, 19, 22, 24, 27, 30, 32, 36, 41, 46 mm	1	6160
0791601005100	791 S10A	Impact Sockets 3/4": 791- 3/4, 7/8, 15/16, 1.1/16, 1.3/16, 1.5/16, 1.7/16, 1.5/8, 1.3/4, 1.7/8" AF	1	6160

You will find the matching OMS-23 module on page no. 48



**792-..., 792A-...**
**IMPACT SOCKET 1", HEXAGON**

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-H 25, ISO 1174
- according to DIN 3129, ISO 2725-2


**25**
**1"**


Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0792000195100	792-19	56	12	35,5	54	7923-45	7924-44	1	684
0792000215100	792-21	56	13	38	54	7923-45	7924-44	1	667
0792000225100	792-22	56	14	39,5	54	7923-45	7924-44	1	672
0792000245100	792-24	57	16	42	54	7923-45	7924-44	1	696
0792000255100	792-25	58	17	43	54	7923-45	7924-44	1	706
0792000265100	792-26	58	17	44,5	54	7923-45	7924-44	1	703
0792000275100	792-27	59	18	45,5	54	7923-45	7924-44	1	691
0792000285100	792-28	58	19	46	54	7923-45	7924-44	1	690
0792000295100	792-29	60	19	48	54	7923-45	7924-44	1	693
0792000305100	792-30	61	20	49,5	54	7923-45	7924-44	1	691
0792000325100	792-32	61	21	52	54	7923-45	7924-44	1	692
0792000335100	792-33	61	21	53	54	7923-45	7924-44	1	686
0792000345100	792-34	62	22	54,5	54	7923-45	7924-44	1	685
0792000365100	792-36	64	24	57	54	7923-45	7924-44	1	746
0792000385100	792-38	64	25	59,5	54	7923-45	7924-44	1	771
0792000415100	792-41	68	26	63	54	7923-45	7924-44	1	787
0792000425100	792-42	68	26	64,5	54	7923-45	7924-44	1	836
0792000465100	792-46	72	28	69,5	54	7923-45	7924-44	1	1133
0792000505100	792-50	76	31	74,5	54	7923-45	7924-44	1	1208
0792000525100	792-52	76	31	76	54	7923-45	7924-44	1	1298
0792000555100	792-55	80	33	80,5	54	7923-45	7924-44	1	1399
0792000605100	792-60	85	36	87	54	7923-45	7924-44	1	1687
0792000655100	792-65	90	39	93	54	7923-45	7924-44	1	2004
0792000705100	792-70	95	41	99,5	54	7923-45	7924-44	1	2280




Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0792100285100	792A-3/4	55	9,5	35	54	7923-45	7924-44	1	582
0792100325100	792A-15/16	55	13	41	54	7923-45	7924-44	1	580
0792100345100	792A-1	55	13	43	54	7923-45	7924-44	1	641
0792100365100	792A-1.1/8	57	16,5	48	54	7923-45	7924-44	1	630
0792100385100	792A-1.1/4	57	17	51	54	7923-45	7924-44	1	630
0792100395100	792A-1.5/16	60	19	54	54	7923-45	7924-44	1	679
0792100405100	792A-1.3/8	60	19	54	54	7923-45	7924-44	1	659
0792100415100	792A-1.7/16	60	19	54	54	7923-45	7924-44	1	631
0792100425100	792A-1.1/2	64	22	60	54	7923-45	7924-44	1	797
0792100445100	792A-1.5/8	64	22	63	54	7923-45	7924-44	1	821
0792100475100	792A-1.13/16	69	25,5	70	54	7923-45	7924-44	1	1013
0792100485100	792A-1.7/8	72	27	70	54	7923-45	7924-44	1	1000
0792100495100	792A-2	72	27	73	54	7923-45	7924-44	1	1080
0792100525100	792A-2.3/16	80	32	82	54	7923-45	7924-44	1	1413
0792100535100	792A-2.1/4	80	33	82	54	7923-45	7924-44	1	1405

## 792LT-...

### IMPACT SOCKET 1", EXTRA DEEP, HEXAGON

- for power tools
- special steel, phosphated
- female square drive according to DIN 3121-H 25, ISO 1174
- inch sizes on request resp. see price list
- special sizes on request, resp. see price list



25

1"



Code	Number	l/mm	l1 mm	d1 mm	d2 mm	Locking Pin	Locking Ring	Pieces	Weight/g
0792020215100	792LT-21	110	18	38	54	7923-45	7924-44	1	957
0792020225100	792LT-22	110	19	39,5	54	7923-45	7924-44	1	973
0792020245100	792LT-24	110	21	42	54	7923-45	7924-44	1	1036
0792020275100	792LT-27	110	23	45,5	54	7923-45	7924-44	1	1075
0792020305100	792LT-30	110	25	49,5	54	7923-45	7924-44	1	1136
0792020325100	792LT-32	110	26	52	54	7923-45	7924-44	1	1208
0792020335100	792LT-33	110	26	53	54	7923-45	7924-44	1	1216
0792020345100	792LT-34	110	27	54,5	54	7923-45	7924-44	1	1236
0792020365100	792LT-36	110	29	57	54	7923-45	7924-44	1	1293
0792020385100	792LT-38	110	30	59,5	54	7923-45	7924-44	1	1398
0792020415100	792LT-41	110	31	63	54	7923-45	7924-44	1	1477
0792020465100	792LT-46	110	33	69,5	54	7923-45	7924-44	1	1798
0792020505100	792LT-50	110	36	74,5	54	7923-45	7924-44	1	2000
0792020555100	792LT-55	110	38	80,5	54	7923-45	7924-44	1	2200
0792020605100	792LT-60	110	41	87	54	7923-45	7924-44	1	2540
0792020655100	792LT-65	110	44	93	54	7923-45	7924-44	1	3000


04



### 792IN-...

#### IMPACT SOCKET 1"

- for power tools
- for inside hexagon screws
- special steel, phosphated
- female square drive according to DIN 3121-H 25, ISO 1174
- inch sizes on request, resp. see price list



25

1"



Code	Number	l/mm	d mm	Locking Pint	Locking Ring	Pieces	Weight/g
0792010105101	792IN-10	100	54	7923-45	7924-45	1	680
0792010125101	792IN-12	100	54	7923-45	7924-45	1	700
0792010145101	792IN-14	100	54	7923-45	7924-45	1	730
0792010175101	792IN-17	100	54	7923-45	7924-45	1	740
0792010195101	792IN-19	100	54	7923-45	7924-45	1	810
0792010225101	792IN-22	100	54	7923-45	7924-45	1	840
0792010245101	792IN-24	100	54	7923-45	7924-45	1	890
0792010275101	792IN-27	100	54	7923-45	7924-45	1	930
0792010305101	792IN-30	100	54	7923-45	7924-45	1	1050
0792010325101	792IN-32	100	54	7923-45	7924-45	1	1260

### 7921-...

#### IMPACT EXTENSION BAR 1"

- for power tools
- special steel, phosphated
- square according to DIN 3121, form F and H, ISO 1174



25

1"

Code	Number	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7921001755100	7921-175	175	7923-45	7924-44	1	1497
7921002505100	7921-250	250	7923-45	7924-44	1	2000
7921003255100	7921-325	325	7923-45	7924-44	1	2200

### 7912-.../7922-.../7932-...

#### IMPACT ADAPTOR

- for power tools
- special steel, phosphated
- square according to DIN 3121, form F and H, ISO 1174



25

1"

Code	Number	□	□	l/mm	Locking Pin	Locking Ring	Pieces	Weight/g
7912100345100	7912-1	3/4"	1"	62	7913-37	7914-36	3	340
7922100285100	7922-3/4	1"	3/4"	75	7923-42	7924-41	1	530
7922100425100	7922-1.1/2	1"	1.1/2"	80	7923-45	7924-44	1	953
7932100345100	7932-1	1.1/2"	1"	95	7933-67	7934-67	1	1975

## 7923-.../7924-...

### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKET 1"

- for locking impact sockets and operating tools
- locking pin made of alloyed special steel
- locking ring made of rubber elastic and oil resistant material



Code	Number	l/mm	mm Ø	Pieces	Weight/g
7923000425100	7923-42	42	5,0	12	6,5
7923000455100	7923-45	45	5,0	12	7,0
7923000515100	7923-51	51	5,0	12	8,0
7924000415100	7924-41	-	41	12	4,0
7924000445100	7924-44	-	44	12	5,0
7924000455100	7924-45	-	45	12	5,5
7924000515100	7924-51	-	51	12	6,0

You will find the matching automotive special sockets on page no. 443



# ! ALL 1.1/2" AND 2.1/2" INSERTS PLUS ACC

04

**793-..., 793A-...**  
**IMPACT SOCKET 1.1/2", HEXAGON**

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square drive according to DIN 3121-H 40, ISO1174
- ▶ according to DIN 3129, ISO 2725-2





40
1.1/2"

**793IN-..., 793INA-...**  
**IMPACT SOCKET 1.1/2"**

- ▶ for power tools
- ▶ for inside hexagon screws
- ▶ with exchangeable blades
- ▶ special steel, phosphated
- ▶ female square drive according to DIN 3121-H 40, ISO 1174





40
1.1/2"

**7933-.../7934-...**  
**IMPACT LOCKING PIN AND RING FOR IMPACT SOCKET 1.1/2"**

- ▶ for locking impact sockets and operating tools
- ▶ locking pin made of alloyed special steel
- ▶ locking ring made of rubber elastic and oil resistant material






# ACCESSORIES ARE AVAILABLE ON REQUEST.

## 793LT-..., 793LTA-...

### IMPACT SOCKET 1.1/2", EXTRA DEEP, HEXAGON

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square drive according to DIN 3121-H 40, ISO 1174



40

1.1/2"




04

## 794-..., 794A-...

### IMPACT SOCKET 2.1/2", HEXAGON

- ▶ for power tools
- ▶ special steel, phosphated
- ▶ female square drive according to DIN 3121-H 63, ISO 1174
- ▶ according to DIN 3129, ISO 2725-2



63

2.1/2"



## 7935-.../7936-...

### IMPACT LOCKING PIN AND RING FOR IMPACT SOCKETS 2.1/2"

- ▶ for locking impact sockets and operating tools
- ▶ locking pin made of alloyed special steel
- ▶ locking ring made of rubber elastic and oil resistant material



**4100-IS...**
**SCREWDRIVER BIT 1/4"**

- for plain slotted screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 E 6,3, DIN ISO 1173
- according to DIN ISO 2351-1


**6,3**
**1/4"**


Code	Number	l/mm	Pieces	Weight/g
4100005045200	4100-IS 0,5x4	50	12	8
4100008045200	4100-IS 0,8x4	50	12	9
4100016085200	4100-IS 1,6x8	50	12	15
4100016095200	4100-IS 1,6x9	50	12	16
4100016115200	4100-IS 1,6x11	50	12	20
4100020125200	4100-IS 2x12	50	12	22

**4120-PH...**
**SCREWDRIVER BIT 1/4"**

- for cross slotted screws PH
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 E 6,3, DIN ISO 1173
- according to DIN ISO 2351-2, tip according to DIN ISO 8764-1 PH


**6,3**
**1/4"**


Code	Number	l/mm	Pieces	Weight/g
412000005200	4120-PH 0	50	12	7,6
412000015200	4120-PH 1	50	12	8,8
412000025200	4120-PH 2	50	12	10,0
412000035200	4120-PH 3	50	12	12,0

**4130-PZ...**
**SCREWDRIVER BIT 1/4"**

- for cross slotted screws PZ
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 E 6,3, DIN ISO 1173
- according to DIN ISO 2351-2, tip according to DIN ISO 8764-1 PZ


**6,3**
**1/4"**


Code	Number	l/mm	Pieces	Weight/g
413000005200	4130-PZ 0	50	12	7,6
413000015200	4130-PZ 1	50	12	8,8
413000025200	4130-PZ 2	50	12	10,8
413000035200	4130-PZ 3	50	12	12,4
413000045200	4130-PZ 4	50	12	18,0

**4110-IN**
**SCREWDRIVER BIT 1/4"**

- for inside hexagon screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 E 6,3, DIN ISO 1173
- according to DIN ISO 2351-3


**6,3**
**1/4"**


Code	Number	l/mm	Pieces	Weight/g
4110000305200	4110-IN 3	50	12	8,4
4110000405200	4110-IN 4	50	12	10,8
4110000505200	4110-IN 5	50	12	11,2
4110000605200	4110-IN 6	50	12	12,8
4110000705200	4110-IN 7	50	12	15,2
4110000805200	4110-IN 8	50	12	16,5
4110001005200	4110-IN 10	50	12	22,4

**4160-TX...**
**SCREWDRIVER BIT 1/4"**

- for inside TORX® screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 E 6,3, DIN ISO 1173
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA


**6,3**
**1/4"**


Code	Number	l/mm	l/mm	Pieces	Weight/g
416000105200	4160-TX10	2,74	70	6	10,4
416000155200	4160-TX15	3,27	70	6	10,4
416000205200	4160-TX20	3,86	70	6	11,6
416000255200	4160-TX25	4,43	70	6	14,8
416000275200	4160-TX27	4,99	70	6	13,2
416000305200	4160-TX30	5,52	70	6	15,2
416000405200	4160-TX40	6,65	70	6	17,6

**3000-IS...**
**SCREWDRIVER BIT 1/4"**

- for plain slotted screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, DIN ISO 1173
- according to DIN ISO 2351-1


**6,3**
**1/4"**


Code	Number	l/mm	Pieces	Weight/g
3000005035200	3000-IS 0,5x 3	39	12	5
3000005045200	3000-IS 0,5x 4	39	12	5,3
3000006355200	3000-IS 0,6x3,5	39	12	6
3000006045200	3000-IS 0,6x4	39	12	5,5
3000006455200	3000-IS 0,6x4,5	39	12	7
3000008045200	3000-IS 0,8x4	39	12	7
3000008555200	3000-IS 0,8x5,5	39	12	7
3000010555200	3000-IS 1,0x5,5	39	12	7,5
3000012655200	3000-IS 1,2x6,5	39	12	11,6
3000012085200	3000-IS 1,2x8	39	12	8,7
3000016085200	3000-IS 1,6x8	39	12	11,6
3000016105200	3000-IS 1,6x10	39	12	15,6

### 3020-PH...

#### SCREWDRIVER BIT 1/4"

- for cross slotted screws PH
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, DIN ISO 1173
- according to ISO 2351-2, tip according to DIN ISO 8764-1 PH



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3020001255200	3020-PH 1x25	25	12	4,8
3020002255200	3020-PH 2x25	25	12	5,2
3020002325200	3020-PH 2x32	32	12	6,9
3020002505200	3020-PH 2x50	50	12	11,6
3020003255200	3020-PH 3x25	25	12	5,2
3020003325200	3020-PH 3x32	32	12	7,2

### 3021-PZ...

#### SCREWDRIVER BIT 1/4"

- for cross slotted screws PZ
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, ISO 1173
- according to ISO 2351-2, tip according to DIN ISO 8764-1 PZ



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3021001255200	3021-PZ 1x25	25	12	5,5
3021002255200	3021-PZ 2x25	25	12	5,6
3021002505200	3021-PZ 2x50	50	12	12
3021003255200	3021-PZ 3x25	25	12	5,6
3021003325200	3021-PZ 3x32	32	12	7,4

### 3010-IN...

#### SCREWDRIVER BIT 1/4"

- for inside hexagon screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, ISO 1173
- according to DIN ISO 2351-3



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3010000305200	3010-IN 3	25	12	5
3010000405200	3010-IN 4	25	12	5
3010000505200	3010-IN 5	25	12	5,4
3010000605200	3010-IN 6	25	12	6,0
3010001005200	3010-IN 10	25	12	11,2

### 3050-TX...

#### SCREWDRIVER BIT 1/4"

- for inside TORX® screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, ISO 1173
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



6,3

1/4"



Code	Number	★ mm	l/mm	Pieces	Weight/g
3050000065200	3050-TX 6	1,69	25	12	4,2
3050000075200	3050-TX 7	1,99	25	12	4,3
3050000085200	3050-TX 8	2,31	25	12	4,4
3050000095200	3050-TX 9	2,5	25	12	4,4
3050000105200	3050-TX 10	2,74	25	12	4,5
3050000155200	3050-TX 15	3,27	25	12	4,6
3050000205200	3050-TX 20	3,86	25	12	5
3050000255200	3050-TX 25	4,43	25	12	5,2
3050000275200	3050-TX 27	4,99	25	12	5,4
3050000305200	3050-TX 30	5,52	25	12	5,6
3050000405200	3050-TX 40	6,65	25	12	6,4

### 3070-TTX...

#### SCREWDRIVER BIT 1/4"

- for inside-TORX® safety screws
- ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, ISO 1173
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



6,3

1/4"



Code	Number	l/mm	★ mm	Pieces	Weight/g
3070000105200	3070-TTX 10	26	2,74	12	4,4
3070000155200	3070-TTX 15	26	3,27	12	4,6
3070000205200	3070-TTX 20	26	3,86	12	4,6
3070000255200	3070-TTX 25	26	4,43	12	5
3070000275200	3070-TTX 27	26	4,99	12	5,4
3070000305200	3070-TTX 30	26	5,52	12	5,4
3070000405200	3070-TTX 40	26	6,65	12	6

### 3050-IPR...

#### SCREWDRIVER BIT 1/4"

- for TORX Plus® IPR-screws
- ELORA-Chrom-Molybdän-Vanadium 73MoV5-2 / 1.2381
- male hexagon according to DIN 3126 C 6,3, ISO 1173
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



6,3

1/4"

Code	Number	l/mm	Pieces	Weight/g
3050000105300	3050-IPR 10	25	12	4,5
3050000155300	3050-IPR 15	25	12	4,6
3050000205300	3050-IPR 20	25	12	5,0
3050000255300	3050-IPR 25	25	12	5,2
3050000275300	3050-IPR 27	25	12	5,4
3050000305300	3050-IPR 30	25	12	5,6
3050000405300	3050-IPR 40	25	12	6,4

### 3030-XZN...

#### SCREWDRIVER BIT 1/4"

- ▶ for inside multi-point B&S and XZN screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon according to DIN 3126 C 6,3, ISO 1173



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3030000055200	3030-XZN M5	25	12	5,2
3030000065200	3030-XZN M6	25	12	5,6

### 3040-RIB...

#### SCREWDRIVER BIT 1/4"

- ▶ for RIBE®-CV-screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 6,3, ISO 1173
- ▶ RIBE® = reg. trademark of Richard Bergner GmbH & Co KG, Schwabach



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3040000055200	3040-RIB M5	32	12	5,0
3040000065200	3040-RIB M6	32	12	6,8
3040000085200	3040-RIB M8	32	12	10,0
3040000105200	3040-RIB M10	32	12	13,2

### 3080-...

#### DOUBLE FUNCTION SCREWDRIVER BIT 1/4"

- ▶ cross-slotted head screws PH
- ▶ 1/4" hexagonal shank
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381



6,3

1/4"



Code	Number	l/mm	Pieces	Weight/g
3080010025260	3080-PH 2	0,8x5,5	12	14
3080010035260	3080-PH 3	1,0x7,0	12	16

### 3100-IS...

#### SCREWDRIVER BIT 5/16"

- ▶ for plain slotted screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173
- ▶ according to DIN ISO 2351-1



8

5/16"



Code	Number	l/mm	Pieces	Weight/g
3100008555200	3100-IS 0,8x5,5	41	12	9,6
3100010555200	3100-IS 1x5,5	41	12	10,4
3100012655200	3100-IS 1,2x6,5	41	12	12,4
3100012805200	3100-IS 1,2x8,0	41	12	16
3100016805200	3100-IS 1,6x8,0	41	12	16
3100020125200	3100-IS 2,0x12	41	12	24
3100025145200	3100-IS 2,5x14	41	12	30

### 3120-PH...

#### SCREWDRIVER BIT 5/16"

- ▶ for cross slotted screws PH
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173
- ▶ according to DIN ISO 2351-2, tip according to DIN ISO 8764-1 PH



8

5/16"



Code	Number	l/mm	Pieces	Weight/g
3120001325200	3120-PH 1x32	32	12	10
3120002325200	3120-PH 2x32	32	12	10
3120003325200	3120-PH 3x32	32	12	11
3120004325200	3120-PH 4x32	32	12	11,5
3120004385200	3120-PH 4x38	38	12	17

### 3121-PZ...

#### SCREWDRIVER BIT 5/16"

- ▶ for cross slotted screws PZ
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon according to DIN 3126 C 8, DIN ISO 1173
- ▶ according to DIN ISO 2351-2, tip according to DIN ISO 8764-1 PZ



8

5/16"




Code	Number	l/mm	Pieces	Weight/g
3121000015200	3121-PZ 1	32	12	10
3121000025200	3121-PZ 2	32	12	10
3121000035200	3121-PZ 3	32	12	10,4
3121000045200	3121-PZ 4	32	12	13,2

### 3110-IN...

#### SCREWDRIVER BIT 5/16"

- ▶ for inside hexagon screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173
- ▶ according to DIN ISO 2351-3



8

5/16"

Code	Number	l/mm	Pieces	Weight/g
3110000045200	3110-IN 4	30	12	9,6
3110000055200	3110-IN 5	30	12	8,9
3110000065200	3110-IN 6	30	12	10,4
3110000085200	3110-IN 8	30	12	12
3110000105200	3110-IN 10	30	12	14,4

### 3150-TX...

#### SCREWDRIVER BIT 5/16"

- ▶ for inside TORX® screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173
- ▶ TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



8

5/16"

Code	Number	mm	l/mm	Pieces	Weight/g
3150000255200	3150-TX 25	4,43	35	12	10,2
3150000275200	3150-TX 27	4,99	35	12	10,4
3150000305200	3150-TX 30	5,52	35	12	10,8
3150000405200	3150-TX 40	6,65	35	12	11,8
3150000455200	3150-TX 45	7,82	35	12	12,9
3150000505200	3150-TX 50	8,83	35	12	14,4
3150000555200	3150-TX 55	11,22	35	12	20,4

### 3130-XZN...

#### SCREWDRIVER BIT 5/16"

- ▶ for inside multi-point B&S and XZN screws
- ▶ ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173



8

5/16"

Code	Number	l/mm	Pieces	Weight/g
3130000055200	3130-XZN 5	28	12	8,4
3130000065200	3130-XZN 6	28	12	8,4
3130000085200	3130-XZN 8	28	12	9,6
3130000105200	3130-XZN 10	32	12	10,4
3130000125200	3130-XZN 12	36	12	22
3130000145200	3130-XZN 14	36	12	31

### 3170-TTX...

#### SCREWDRIVER BIT 5/16"

- ▶ for inside-TORX® safety screws
- ▶ ELORA Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- ▶ male hexagon drive according to DIN 3126 C 8, DIN ISO 1173
- ▶ TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



8

5/16"

Code	Number	mm	l/mm	Pieces	Weight/g
3170000255200	3170-TTX 25	4,43	35	12	10
3170000275200	3170-TTX 27	4,99	35	12	10
3170000305200	3170-TTX 30	5,52	35	12	11

### 3090

#### BIT RATCHET, STRAIGHT

- ▶ bit lock with permanent magnet
- ▶ reversible
- ▶ female hexagon drive according to DIN 3126 D 6,3 (1/4") and DIN 3126 D 8 (5/16")



6,3

8

1/4"

5/16"

Code	Number	l/mm	Pieces	Weight/g
3090000002000	3090	138	6	105

### 3090G

#### BIT RATCHET, CRANKED

- ▶ bit lock with permanent magnet
- ▶ reversible
- ▶ female hexagon drive according to DIN 3126 D 6,3 (1/4") and DIN 3126 D 8 (5/16")



6,3

8

1/4"


5/16"

Code	Number	l/mm	Pieces	Weight/g
3090000102000	3090G	140	6	105

### 3415

#### HAND BIT HOLDER 1/4"

- ▶ bit lock with permanent magnet
- ▶ nonslip QUATROLIT®-2C-handle
- ▶ with suspension hole
- ▶ ELORA-Chrome-Vanadium 31CrV3 / 1.2208
- ▶ female hexagon drive according to DIN 3126 D 6,3 DIN ISO 1173




Code	Number	l/mm	⊙	Pieces	Weight/g
341500000000	3415	180	1/4"	6	130

### 3300-...

#### ADAPTOR FOR SCREWDRIVER BITS

- ▶ for power tools
- ▶ bit lock with spring clip
- ▶ gunmetal finished
- ▶ ELORA-Chrome-Vanadium Steel 31CrV3 / 1.2208
- ▶ female hexagon drive according to DIN 3126 D 6,3 respectively DIN 3126 D 8; DIN ISO 1173
- ▶ female square drive according to DIN 3121 Form G
- ▶ according to DIN 7427 Form A




Code	Number	⊙	⊙	l/mm	Pieces	Weight/g
3300123132000	3300-1/2x1/4	1/2"	1/4"	35	6	80
3300123172000	3300-1/2x5/16	1/2"	5/16"	35	6	64

### 4150-...

#### BITHOLDER 1/4"

- ▶ bit lock with permanent magnet resp. spring clips
- ▶ with stainless steel sleeve, diameter 9,5 mm
- ▶ female hexagon drive according to DIN 3126 D 6,3
- ▶ male hexagon drive according DIN 3126 E 6,3 DIN ISO 1173
- ▶ according to DIN 7427 Form D




Code	Number	l/mm	⊙	⊙	Pieces	Weight/g
4150000505200	4150-50	50	1/4"	1/4" with spring clip and magnet	6	26
4150001005200	4150-100	100	1/4"	1/4" with spring clip and magnet	6	39

### 3428

#### BITHOLDER 1/4"

- ▶ bit lock with permanent magnet and quick clamping system
- ▶ quick locker and ejection system
- ▶ female hexagon drive according to DIN 3126 D 6,3
- ▶ male hexagon drive according DIN 3126 E 6,3, DIN ISO 1173




Code	Number	l/mm	⊙	Pieces	Weight/g
3428000000000	3428	51	1/4"	6	24

### 3429

#### BITHOLDER 1/4"

- ▶ with strong permanent magnet for holding the bit
- ▶ bit lock due to quick clamping system and ejection function
- ▶ female hexagon drive according to DIN 3126 D 6,3 and F 6,3
- ▶ male hexagon drive according DIN 3126 E 6,3, DIN ISO 1173




Code	Number	l/mm	⊙	Pieces	Weight/g
3429000000000	3429	60	1/4"	6	27

### 3452ST

#### BIT-BOX, STAINLESS 1/4"

- 19 pcs.
- bit holder ELORA-No. 3428 with quick clamping system and male hexagon drive according to DIN 3126 E 6,3
- bits made of stainless steel X46Cr13 / 1.4034, without galvanic surface treatment
- 18 bits with male hexagon drive according to DIN 3126 C 6,3




Code	Number	Contents	Pieces	Weight/g
3452500008000	3452ST	1 Magnetic quick action bit holder ELORA-No.3428 2 piece each plain slotted Screwdriver Bits 0,8x5,5, 1,0x5,5, 1,2x5,5 mm 2 piece each Philips Screwdriver Bits PH1, PH2, PH3 2 piece each Pozidriv Screwdriver Bits PZ1, PZ2, PZ3	1	180

### 3451-S9

#### BIT-BOX 1/4"

- 9 pcs.
- in black plastic box with transparent cover
- magnetic bit holder ELORA-No. 4150-50, with male hexagonal drive according to DIN 3126 E 6,3
- bits made of ELORA-Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- 8 bits with male hexagon drive according to DIN 3126 C 6,3




Code	Number	Contents	Pieces	Weight/g
3451500000000	3451-S9	1 Magnetic bit holder ELORA-No.4150-50 1 piece each plain slotted Screwdriver Bit 4,5x0,6, 6,5x1,2 mm 1 piece each Philips Screwdriver Bit PH1, 2x PH2 1 piece each Pozidriv Screwdriver Bit PZ1, 2x PZ2	1	108

04

### 3436-S36

#### BIT-BOX 1/4"

- 36 pcs.
- in black yellow plastic box with belt clip and suspension hole
- magnetic bit holder ELORA-No. 4150-50, with male hexagonal drive according to DIN 3126 E 6,3
- bits made of ELORA Chrome-Molybdenum-Vanadium 73MoV5-2 / 1.2381
- 35 bits with male hexagon drive according to DIN 3126 C 6,3
- TORX® = reg. trademark of Acument Intellectual Properties, LLC. USA



Code	Number	Contents	Pieces	Weight/g
3436000000000	3436-S36	1 Magnetic bit holder ELORA-No. 4150-50 1 piece each each plain slotted Screwdriver Bit 4,5, 5,5, 6,5 mm Phillips Screwdriver Bits 2x PH1, 3x PH2, 2x PH3 Pozidriv Screwdriver Bits 2x PZ1, 3x PZ2, 2x PZ3 1 piece each Inside hexagon Screwdriver Bit IN2, IN 2,5, IN3, IN4, IN5, IN5,5, IN6 1 piece each TORX®-Screwdriver Bit TX10, TX15, TX20, TX25, TX27, TX30, TX40 1 piece each TORX®-Screwdriver Bit TTX20, TTX25, TTX30 TTX40	1	340

### 3400

#### HAND OPERATED IMPACT DRIVER 1/2"

- for loosening tight screws with help of a hammer
- reversible with anti-slip plastic grip
- male square drive according to DIN 3120-A 12,5, ISO 1174, with ball locking device



12,5

1/2"

Code	Number	l/mm	Pieces	Weight/g
3400000000000	3400	150	1	750

### 3401-S12

#### HAND OPERATED IMPACT DRIVER SET

- 12 pcs.
- in black metal case with plastic inlet
- for loosening tight screws with help of a hammer
- reversible with anti-slip plastic grip
- male square drive according to DIN 3120-A 12,5, ISO 1174, with locking device



Code	Number	Contents	Pieces	Weight/g
3401500120000	3401-S12	1 Hand Operated Impact Driver ELORA-No. 3400 1 Adaptor 3300-1/2x5/16 1 piece each Screwdriver Insert Bit, Plain Slot, 3100-IS 1,0x5,5, 1,2x6,5, 1,6x8,0, 2,0x12,0 mm 1 piece each Screwdriver Insert Bit, cross slot, 3120-PH 2x32, PH 3x32, PH 4x32 1 piece each Screwdriver Insert Bit, inside hexagon 3110-IN 6, IN 8, IN 10 mm	1	1385